

The content in this preview is based on the last saved version of your email - any changes made to your email that have not been saved will not be shown in this preview.

[View as Webpage](#)



We Invent, Manufacture, and Customize  
Unique Lighting Accessories

[HOME](#)

[EXPERIENCE](#)

[PRODUCTS](#)

[DEALERS](#)

[VIDEOS](#)



## QolorFLEX 25x3A Dimmer and new! 6617 Seven-Pin Connectors

City Theatrical's [QolorFLEX® 25x3A Dimmer](#) (P/N 5811) features 25 channels of control and can accommodate five-channel LED tapes easily, including [QolorFLEX 5-in-1 LED Tapes](#), to create efficiencies when it comes to installation time and wiring.



The 5811 dimmer was recently updated to now include five removable [New! Terminal Block Connectors, Seven Pin, Female](#) (P/N 6617) for LED output connections. The new 6617 seven-pin connectors include five channels and two V+ commons. This change will allow end users to spread the load of multiple LED tapes over the two positive outputs and achieve a maximum current load per channel of 4A.

This dimmer's power connection is one removable [Terminal Block Connector, Eight Pin, Male](#) (P/N 6614) for DC Input.

## Terminal Block Connectors


Available Through City Theatrical:



Eight Pin, Male (6614)



**New!** Seven Pin, Female (6617)



Six Pin, Male (6612)



Six Pin, Female (6613)



Five Pin, Male (6610)



Five Pin, Female (6611)



Four Pin, Male (5673)



Four Pin, Female (5674)



Three Pin, Male (5671)



Three Pin, Female (5672)



Two Pin, Male (5657)



Two Pin, Female (5657)



The [QolorFLEX 25x3A Dimmer](#) is fully DMX and RDM compatible and offers standalone functions. The DMX connections include 5-Pin XLR, 3-Pin XLR, and etherCON RJ45 connectors, which are a ruggedized and lockable RJ45 connector system, optimized for pro audio, video and lighting network applications. The QolorFLEX 25x3A Dimmer also includes 99 curve selection options and 18 film and video modes. This dimmer requires an external power supply to suit the LED tape being used. It is designed for indoor use. This driver has a Maximum Device Input of 75A.



[www.citytheatrical.com](http://www.citytheatrical.com)



### City Theatrical, LLC

201.549.1160  
800.230.9497

### City Theatrical Ltd. (Europe)

+44 (0)20 8949 5051

[USA Email](#)

[Europe Email](#)

© 2024 City Theatrical. All Rights Reserved.



City Theatrical, Inc. | 475 Barell Avenue | Carlstadt, NJ 07072 US

[Unsubscribe](#) | [Update Profile](#) | [Constant Contact Data Notice](#)