

An Environmental Lights Company



QolorFLEX® 24x3A Dimmer (P/N 5810) is a low voltage, constant voltage, dimmer that is ideal for applications such as retail displays, signage, and general architectural work. It features 24 channels of control and is ideal for one-, two-, three- or four-color LED tape installations. This dimmer is fully DMX and RDM compatible and offers standalone functions.

The QolorFLEX 24x3A Dimmer's maximum current load per channel is 3A with a Maximum Device Input of 72A. It requires an external power supply to suit the LED tape you are using. For indoor use.





QolorFLEX 24x3A Dimmer shown controlling QolorFLEX LED Tape (left) and QolorFLEX® NuNeon (right).

Accessories:

6611

Terminal Block Connector, Five Pin, Female



(Six connectors are included with 5810)

QolorFLEX® 24x3A Dimmer P/N 5810

SPECIFICATIONS:

Physical		
Length	26.0 cm	(10.24 in)
Width	12.0 cm	(4.72 in)
Height	4.0 cm	(1.57 in)
Weight	0.86 kg	(1.9 lbs.)
Construction	Steel	
User Interface	4 button, plus alpha/ numeric display	

Electrical	
Output Channels	24
Input Voltage	12~24VDC
Max Output Per Channel	3A
Max Device Input	72A
Power Connections	Screw Terminals
Output Connections	Screw Terminals
DMX Connections	5 Pin XLR, RJ-45
0-10 Connections	No
DMX Address	Yes
Curve Selection	Yes - 99
Film & Video Modes	Yes - 18
DMX Termination	No
SHoW ID	N/A
Bump Buttons	No
Pilot Lights	Yes
Smoothing Settings	No
Standalone Levels	Yes
RDM	Yes

Product Information	
Use Environment	Indoor
Warranty	One year
Compliance	CE, RoHS