



Multiverse Connect Module, 900MHz (P/N 5915) is a small device that brings all the capabilities of Multiverse wireless DMX/RDM on the 900MHz band* to a lighting fixture built by an OEM manufacturing partner of City Theatrical, such that the fixture has a Universal Connect Module socket built into it. The chassis of the device plugs into the fixture, and with a few menu changes on your fixture, it becomes wireless.

Multiverse Connect Modules are Multiverse wireless DMX/RDM receivers encased in ABS plastic and use a 1.8dBi/3.8dBi Omni Broadband “Stubby” Antenna (P/N 5984), like the Multiverse Studio Receiver wireless DMX/RDM solution.

Multiverse Connect Modules include seamless RDM integration and can be configured through host fixture UI/RDM. The Multiverse Connect Modules uses a USB Type-C Plug connector and runs on 5VDC. The Multiverse Connect Module is IP64 rated and can be used in an indoor or outdoor environment.

Multiverse transceivers are covered by U.S. Patents #7,432,803 B2, #10,129,964 B1, and other patents pending.

*900MHz is licensed for use in North America only.

Antenna:
1.8dBi/3.8dBi Omni Broadband
Antenna (P/N 5984)



**Multiverse® Connect Module,
900MHz (P/N 5915)**

SPECIFICATIONS:

P/N	Frequency	Universes
5915	900MHz	1

Physical

Length	55.4 mm	(2.2 in)
Width	40.4 mm	(1.6 in)
Height	39.2 mm	(1.5 in)
Antenna	2dBi/4dBi Omni Broadband Antenna, 900MHz/2.4GHz (5980)	
Construction	ABS Plastic	
Power/Data Connection	USB-C	
Signaling	USB 2.0	

Product Information

Voltage Range	5VDC
Current Consumption	25 mA @ 5VDC
Broadcast Power	Antenna dependent; 100mW EIRP
Broadcast Modes	Adaptive, Full, Low, Mid
SHoW IDs	Multiverse: 90
Latency	4ms average
RF Sensitivity	-95dBm
RDM Features	Seamless RDM Integration
Configuration	Through host fixture UI/RDM
Use Environment	Indoor, Outdoor
IP Rating	IP64
Warranty	One year
Compliance	FCC, IC

