



SPECIFICATIONS:

P/N	Frequency	Universes
5943	2.4GHz	1


Physical		
Length with Antenna	10.0 cm (3.94 in)	14.3 cm (5.63 in)
Width with Phoenix Connectors	5.9 cm (2.31 in)	7.0 cm (2.75 in)
Height	1.6 cm (0.63 in)	
Weight	0.07 kg (0.15 lbs.)	
Construction	NEMA 4 IP20 ABS Plastic	
Connections	Pluggable connectors	
Mounting	Plastic bracket included	

Dimming Information	
Voltage Range	5 - 30 VDC
PWM Frequencies (Hz)	60, 1.2K, 2.4K, 5K, 12K, 24K, 50K
Power	4A/channel maximum; 12.5A total
Control Resolution	6 DMX Personality options, including: 8-bit (5ch), 16-bit (10ch), 8-bit Tunable White Single (2ch), 16-bit Tunable White Single (4ch), 8-bit Tunable White (4ch), 16-bit Tunable White (8ch)
PWM Resolution	20-bit



QolorFLEX®

QolorFLEX® 5x2.5A 2.4GHz Multiverse® Dimmer (P/N 5943) is a constant voltage, five-output dimmer that can be controlled wirelessly (with Multiverse Technology), or with wired DMX. This dimmer provides 20-bit PWM resolution and six DMX personality options (including: 8-bit (5ch), 16-bit (10ch), 8-bit Tunable White Single (2ch), 16-bit Tunable White Single (4ch), 8-bit Tunable White (4ch), and 16-bit Tunable White (8ch)) for extremely smooth dimming at the low end of the dimming curve. It uses detachable input and output connectors to make wiring easy. Configuration is performed using RDM, such as with a City Theatrical DMXcat®, or with City Theatrical's USB Configuration program for PC/Mac. A mounting bracket is included with the Dimmer to allow easy mounting to scenery. This dimmer is designed and built in the USA by City Theatrical. It pairs perfectly with QolorFLEX 5-in-1 LED Tape for ideal use in props and costumes, or for areas where space is a concern.





*Multiverse Transceivers are covered by U.S. Patent # 7,432,803 and other patents pending.

Radio Information

Broadcast Power	Antenna dependent; 100mW EIRP
Broadcast Modes	Adaptive, Full, Low, Mid, High, Max
Ethernet Protocols	N/A
SHoW IDs	Multiverse: 147; Neo: 70
Latency	4ms average
RF Sensitivity	-95dBm
Antenna	Omni broadband, 2.4GHz 3.8dBi
RDM Features	RDM Proxy, RDM Responder

Product Information

Firmware	User updateable via micro USB
Configuration	RDM, City Theatrical USB Configuration Program (PC/Mac)
Use Environment	Indoor
Warranty	One year
Manufacturing Origin	USA
Compliance	CE, RoHS, FCC, ACMA, ARIB, IC

FEATURES:

- Wireless or wired DMX input
- Wired DMX output
- Mounting bracket included
- Compatible with Multiverse 2.4GHz and SHoW DMX Neo SHoW IDs
- DMX termination selector switch
- Per channel level indicator lights
- Per channel PWM frequency, response time, and curve selections
- Per channel bump buttons, with disable function
- Per channel offsets to balance the point at which each dimmer first turns on (important for perfect low end balance)
- DMX data loss options
- Micro USB port for firmware updates and configuration
- Class 2 outputs
- Error detection and signal light for short circuits, over current, over/under voltage, over temperature
- Six DMX personality options for extremely smooth dimming at the low end of the dimming curve