




The **Multiverse® Vero Transceiver 900MHz/ 2.4GHz** brings the advanced features of the Multiverse wireless DMX/RDM system to outdoor installations for architecture and entertainment. The 7400-5902 Multiverse Vero Transceiver 900MHz/2.4GHz contains two radios, 2.4GHz (for worldwide use) and 900MHz (for use in the Americas only), which allow the user to select which single universe to receive, and which radio band to use via the Multiverse SHoW ID.

The Multiverse Vero Transceiver is housed in a NEMA 4 / IP66 package that provides protection from the outdoor elements. Its internal backlit LCD display makes setup easy and gives feedback on system performance. Each unit comes with a dual band 2.5dBi outdoor omni-directional Antenna.



**Multiverse® Vero Transceiver
900MHz/2.4GHz**

SPECIFICATIONS:

P/N	Frequency	Universes
7400-5902	900MHz*/2.4GHz	1

Physical

Height (unit only)	165.0mm	(6.5 in)
Width	152.0mm	(6.0 in)
Depth	102.0mm	(4.0 in)
Weight	0.77kg	(1.70 lbs)
Antenna	Dual band 900MHz / 2.4GHz 2.5dBi / 2.5dBi	
User Interface	Internal Backlit LCD display	
Construction	NEMA 4 / IP66 Aluminum enclosure	
EPA	0.3125ft ²	

Electrical

Power	90-277VAC input, 1A max, on 3 pin screw terminals	
DMX	DMX In and Out via 3 pin screw terminals	

Radio Technology

Latency	4 ms average	
RF Sensitivity	-95dBm	
Loss of Data Behavior	Output stops	
Broadcast Power	3.2mW, 10mW, 32mW, 100mW EIRP	
Broadcast Modes	Adaptive, Full, Low, Mid, High, Max	
Show IDs	Multiverse: 307; Neo: 70	
RDM Features	RDM Proxy, RDM Responder	

Product Information

Use Environment	Indoor or outdoor	
IP Rating	IP66	
Compliance	FCC, IC, cETLus Listed	
Warranty	One year	

*The 900MHz band is licensed for use in North America only.