

CITY THEATRICAL

NEW YORK • LONDON

475 Barell Ave., Carlstadt, NJ 07072
Voice: 800-230-9497, 201-549-1160
Fax: 201-549-1161

QFlood 7500™ Wireless LED Floodlight

CTI Part #: 7070 QFlood 7500™ Wireless LED Floodlight

The **QFlood 7500™** is a high-brightness, battery powered portable LED illumination unit, fully rated for outdoor use (IP65) with high powered neutral white LEDs. At over 7,500 lumens (equivalent to 750W tungsten halogen) the QFlood 7500™ is designed for instant illumination anywhere. It can be powered or charged from line voltage, and folds to a compact 10" (25cm) cube. The head may be stand mounted on the base unit or off the unit with multiple accessories.



The QFlood 7500™ features include:

- Extreme white LED output 7500 lumens
- Fully sealed IP65 for outdoor use
- Folds to a 10" (25cm) cube
- Four hour usage duration at full power, eight hours at 50% power
- Recharges in eight hours
- Can be powered off line voltage for continuous use
- Lithium ion battery
- Removable head for mounting on attachable stand
- Head closes onto body for ruggedness, protection and portability

Mechanical

- IP65 for outdoor use
- Rugged powder coated aluminium housing and head
- Lock and/or chain through handles for security (not supplied).

Settings

- Manual

Compliance

- CE, FCC & RoHS Compliant
- CE Certified



Specifications:

Application	Outdoor/indoor
Wireless Control	N/A
Wireless Range	N/A
SHoW DMX SHoW IDs	N/A
Runtime Fully Charged	4 hours full power, 8 hours at 50% power
Recharge Time	8 Hrs
Light Output	7500 Lumens
Beam Angle	22°
Color Type	Neutral White
Color Temp	4,000°K
Operating Temp	-4° F to 113° F
Input Power (Charging)	120-240VAC
Battery Type	Li-Ion
Power Connectors	Neutrik Powercon
Data Connectors	N/A
Dimensions	10" W. x 10" D. x 10" H. (250mm W. x 250mm D. x 200mm H.)
IP Rating	65
Weight	20 lbs (9.0 Kg)
Compliance	CE
PWM	N/A